





EARTHING BRAID

Customization

Customized colour option and printing of the outer sheath on request

Flat/Round

RJ 1501



Product Description:

We are Offering a wide range of Earthing Cable which uses Rod to Cable Lug Clamp, Cable Clamp and many more. All the materials are well tested and meet with the highest quality standards.

Make up:

- Strands of tinned copper wires
- Flat around sleeves, having strands of tinned copper wire
- Shaped & welded end /pressed contact (optional)

Approvals:



Technical Data:

- Conductor stranding**
 Harnessed Ground Straps
 IEC 60 228 Class 6
 Harness Flat Ground Straps
 IEC 60 228 Class 6, tinned
 Extra fine wire
- Minimum bending radius**
 Harness Ground Straps
 7 x outer diameter
 Harness Flat Ground Straps
 5 x outer diameter

Application Range:

- Switch cabinet building.
- The protective earth safety measure is prescribed by standard.
- Fixed and moving metal parts such as door in switch cabinet building must be earthed.

Part number	Braid Size	Approx Area Sqmm	Makeup	Copper index kg/km	Weight kg/km
RJ 1501					
1501 00801	2x4	0.75	Round	9.50	7.2
1501 00901	4x5	1.50		18.00	14.0
1501 01001	3x6	1.80		22.20	17.0
1501 01101	6x10	3.00		36.70	28.0
1501 01201	10x16	6.00		76.60	58.0
1501 01301	16x24	14.00		178.00	134.0
1501 01401	24x30	20.00		213.00	192.0
1501 01501	6	1.75	Flat	85.00	16.0
1501 01601	12	4.50		85.00	41.0
1501 01701	19	7.50		85.00	70.0
1501 01801	25	9.50		85.00	90.0